

# PMLC-LED

## Construction:

- Steel housing and chassis
- Elliptical white smooth acrylic bowl is standard
- Optional alabaster bowl

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Chassis mounts to standard J-Box
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### PMLC-24-LED

Height - 7"  
Width - 24"

### PMLC-36-LED

Height - 10"  
Width - 36"



## ORDERING INFORMATION

Example: PMLC-36-LED-O12C-3-Z1-WSA

### PMLC

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options		
24-LED	L1A	36	4000	0-10v	NO	2 3000K 4 4000K  Optional 3 3500		B1 Satin Black	WSA WhiteSmooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory		
	O6C	54	7260	0-10v	NO			B2 Text Black			Optional Lens Material (see Price List)	
	O8C	72	9680	0-10v	NO			Z1 Satin Bronze				AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster
	O9C	80	10890	0-10v	NO			Z3 Text Bronze				
36-LED	L1A	36	4000	0-10v	NO		W1 Yolk White		90CRI Consult Factory			
	O6C	54	7260	0-10v	NO		W2 Gloss White					
	O8C	72	9680	0-10v	NO		T4 Shimmer Gray					
	O12C	107	14520	0-10v	NO		M13 Anod Silver					
	O18C	160	21780	0-10v	NO		T6 Pewter					
							Optional (See Price List)			Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes		
								M17 Brass Powder				



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

