

NASW-LED

Construction:


- Steel housing
- Diffuser is .060" thick white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts to Standard J-box – hardware included
- Optional battery backup - Requires 1 3/4" extension ring
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



Battery Backup option

NASW-13

DIM 'A' - 12 7/8"
DIM 'B' - 3"

NASW-17

DIM 'A' - 17"
DIM 'B' - 3 5/8"

NASW-19

DIM 'A' - 20 5/8"
DIM 'B' - 4"



ORDERING INFORMATION

Example: NASW-17-LED-F1Q-4-W2-WSA

NASW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
13-LED	F1L	9	1400	0-10v	YES	2 3000K 4 4000K		W2 Gloss White	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page ES Energy Star listed components 90CRI Consult Factory OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minute
	F1O	10	863	TRIAC/ELV	YES	Optional 3 3500K				
	F1P	15	1361	TRIAC/ELV	YES					
17-LED	F1K	13	2115	0-10v	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1Q	23	2057	TRIAC/ELV	YES					
19-LED	L1A	36	4000	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

