

MDAW-6xx-LED

Construction:


- Steel chassis and cage
- Diffuser is impact resistant extruded white acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate; keyhole slots
- Top and bottom white acrylic lens - standard
- Optional photocell (21) increases fixture depth 3/4"
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



MDAW-616

MDAW-626

MDAW-638

MDAW-650

DIM 'A'	M.C.
16"	8"
26"	13"
38"	19"
50"	25"

Type:	
Job Name:	



ORDERING INFORMATION

Example: MDAW-626-LED-O2C-4-Z3-WSA

MDAW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
616-LED	O1C	9	1210	0-10v	NO	2 3000K		B1 Satin Black	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v)
626-LED	O2C	18	2420	0-10v	NO	3 3500K		B2 Text Black		
638-LED	O3C	27	3630	0-10v	NO	4 4000K		Z1 Satin Bronze		
650-LED	O4C	36	4840	0-10v	NO	5 5000K		Z3 Text Bronze		
								W1 Yolk White		
								W2 Gloss White		21 Photocell - See Notes
								T4 Shimmer Gray		-01 120 volt
								M13 Anod Silver		-02 277 volt
								T6 Pewter		Optional Voltage
								W13 Pearl Beige		-347V Input voltage to 347v
								Optional		
								(See Price List)		
								M17 Brass Powder		Battery Backup Options
								P2 Brushed Alum		(Available with 0-10v only)
										BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
800-325-4448 / 661-257-0286
www.lightwayind.com • sales@lightwayind.com



Revision: 07/23/2025