

BUXW-LED

Construction:

- Steel housing and chassis
- Optional Aluminum construction

Light Source:


- LED
- Dimming to 10% **Included**

Notes:

- Universal mounting plate
- Up/Down Light
- Optional Aluminum construction
- Optional battery backup increases depth to 4"
- ADA compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:

Job Name:



-39 J-Box Option

BUXW-9

Height - 9 1/4"

Width - 4 3/4"

Depth - 2 3/4"

Mounting Center - 4 1/2" from the Bottom



ORDERING INFORMATION

Example: BUXW-9-LED-F2B-4-Z1-42

BUXW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K				
9-LED	F2B	12	1180	0-10v	NO			B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder M16 Antique Brass P2 Brushed Alum P9 Brushed Nickel		DIM LED dimming driver (0 - 10v) 39 Surface mounted Jbox with knockouts 42 All Aluminum Construction Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
• 50% Up / 50% Down										



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com



Revision: 08/12/2025