

# SGRW-LED

## Construction:

- Aluminum housing and chassis
- Front shield is steel

## Light Source:

- LED

## Notes:

- Center lockup – hardware included
- Solid top and open bottom
- Optional clear or white smooth acrylic lens
- Bug Rating: B0-U0-G0
- Light source is recessed more than 2" from the bottom
- ADA compliant
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

|           |  |
|-----------|--|
| Type:     |  |
| Job Name: |  |



## SGRW-7-LED

Height - 7"

Width - 12"

Depth - 4"



## ORDERING INFORMATION

Example: SGRW-7-LED-F1C-4-B1

## SGRW

| Size  | LED |       |               |         |             | Kelvin              | Cage | Finish  | Diffuser | Options  |
|-------|-----|-------|---------------|---------|-------------|---------------------|------|---|----------|--|
|       |     | Watts | Source Lumens | Dimming | Energy Star | 2 3000K<br>4 4000K  |      | <b>B1</b> Satin Black<br><b>B2</b> Text Black<br><b>Z1</b> Satin Bronze<br><b>Z3</b> Text Bronze<br><b>W1</b> Yolk White<br><b>W2</b> Gloss White<br><b>T4</b> Shimmer Gray<br><b>M13</b> Anod Silver<br><b>T6</b> Pewter<br><b>W13</b> Pearl Beige<br><br><b>Optional</b><br>(See Price List)<br><b>M17</b> Brass Powder<br><b>M16</b> Antique Brass<br><b>P2</b> Brushed Alum<br><b>P9</b> Brushed Nickel |          | <b>DIM</b> LED dimming driver (0 - 10v)<br><b>DIMLD</b> Line Voltage /TRIAC/ELV/120v<br>Consult Factory<br><br><b>ES</b> Energy Star listed components<br><b>90CRI</b> Consult Factory<br><br><b>Battery Backup Options</b><br>(Available with 0-10v only)<br><b>BB10</b> 10 Watts (1170lm) for 90-Minutes |
| 7-LED | F1C | 10    | 1518          | 0-10v   | NO          | Optional<br>3 3500K |      |   |          |  |



28435 Industry Drive., Valencia, California 91355  
 800-325-4448 /661-257-0286  
 www.lightwayind.com • sales@lightwayind.com

