

SMNW-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster acrylic lenses

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SMNW-12	SMNW-15	SMNW-22
Height - 12"	Height - 13 ¾"	Height - 18 ½"
Width - 8"	Width - 10"	Width - 15"
Depth - 5 ¼"	Depth - 5 ½"	Depth - 7 ½"



ORDERING INFORMATION

Example: SMNW-22-LED-O2C-4-Z1-WTP

SMNW

Size	LED	Watts	Source Lumens	Dimming	Energy Star	Kelvin	Cage	Finish	Diffuser	Options
12-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K		B1 Satin Black B2 Text Black	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page 90CRI Consult factory ES Energy Star listed components 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
	F1O	10	863	TRIAC/ELV	YES	Optional 3 3500K		Z1 Satin Bronze Z3 Text Bronze		
	F1P	15	1361	TRIAC/ELV	YES			W1 Yolk White W2 Gloss White		
	F1J	20	2820	0-10v	YES			W3 Text White T4 Shimmer Gray		
	15-LED	F1H	9	1400	0-10v			YES	T6 Pewter W13 Pearl Beige	
F1O		10	863	TRIAC/ELV	YES					
O2B		15	2000	0-10v	NO					
F1P		15	1361	TRIAC/ELV	YES					
F1J		20	2820	0-10v	YES					
22-LED	F1H	9	1400	0-10v	YES					
	O2C	18	2420	0-10v	NO					



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

