

JPBP-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured polycarbonate.

Light Source:

- LED

Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- Integral Driver slips in 3" round pole - Requires minimum 10" depth in pole
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



JPBP-13

Height - 13"
Width - 11"
Depth - 12.8"



ORDERING INFORMATION

Example: JPBP-13-LED-01J-4-B1-WTP

JPBP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	Pole Options (see supplemental spec sheet on website and price list) 42 All Aluminum Construction 90CRI Consult Factory Optional Voltage -347V Input voltage to 347v
13-LED	F2B	12	1180	0-10v	NO					
								Optional (See Price List) M17 Brass Powder M16 Antique Brass		



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

