

# BPRW-LED

## Construction:

- Steel top, bottom and rings
- Cylinder is .125" thick white smooth acrylic

## Light Source:

- LED
- Dimming to 10% **Included**


## Notes:

- Integral mounting plate for standard "J-Box"
- Standard mounting orientation is upward
- For optional downward mounting consult factory
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components


Type:	
Job Name:	



**BPRW- 16 - 20 - 25**  
 Height - 15" - 19" - 24"  
 Width - 7 1/4" 8 1/2" 10"  
 Depth - 9 3/4" 11" 13"



Upward Mounting  
(MU)



Downward Mounting  
(MD)



## ORDERING INFORMATION

**Example: BPRW-16-LED-O4C-4-Z3-WSA-MU**

### BPRW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>M13</b> Anod Silver <b>T4</b> Shimmer Gray <b>T6</b> Pewter <b>W1</b> Yolk <b>W2</b> Gloss White <b>W3</b> Text White <b>W13</b> Pearl Beige <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze	<b>WSA</b> White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% ( <b>Included</b> )
<b>16-LED</b>	<b>O4C</b>	36	4840	0-10v	NO	<b>Optional</b> 3 3500K				<b>MU</b> Mounted Upward (Standard) <b>MD</b> Mounted Downward (Consult Factory for Lamping Options)
	<b>1E26</b>		0	TRIAC/ELV	NO					
<b>20-LED</b>	<b>O4C</b>	36	4840	0-10v	NO					
<b>25-LED</b>	<b>O8A</b>	48	6400	0-10v	NO					



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

