

# VTWV-LED

## Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic


## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Mounts to standard J-Box with slotted anchor holes
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 90
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



Length - 24"  
Height - 5"  
Depth - 5 3/8 "



## ORDERING INFORMATION

Example: VTWV-24-LED-F2EL-4-W2-WSA

VTWV

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		<b>B1</b> Satin Black <b>B2</b> Text Black <b>Z1</b> Satin Bronze <b>Z3</b> Text Bronze <b>W1</b> Yolk White <b>W2</b> Gloss White <b>W3</b> Text White <b>T4</b> Shimmer Gray <b>M13</b> Anod Silver <b>T6</b> Pewter <b>W13</b> Pearl Beige	<b>WSA</b> White Smooth Acrylic	<b>DIMLD</b> Line Voltage /TRIAC/ELV/120v Consult Factory
<b>24-LED</b>	<b>F1Y</b>	30	3235	TRIAC/ELV	YES	<b>Optional</b> 3 3500K	<b>Optional</b> (See Price List)			<b>ES</b> Energy Star listed components <b>T24</b> Title 24/JA8 Compliant (F1Y configuration only)



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

