

# JPTP-LED

## Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured or optional white smooth polycarbonate.
- Optional alabaster lenses are .080" thick acrylic

## Light Source:

- LED

## Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



### JPTP-16

Height - 15 1/2"  
Width - 11 1/2"  
Depth - 11 1/2"

### JPTP-18

Height - 18 1/2"  
Width - 13 1/2"  
Depth - 13 1/2"



## ORDERING INFORMATION

Example: JPTP-18-LED-O4C-4-B1-AHA

### JPTP

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
16-LED	O4B	29	4000	0-10v	NO	2 3000K 3 3500K 4 4000K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate	Pole Options (see supplemental spec sheet on website and price list)	
	O4C	36	4840	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					
18-LED	O4B	29	4000	0-10v	NO		Optional (See Price List) M17 Brass Powder M16 Antique Brass	Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate		
	O4C	36	4840	0-10v	NO					
	1E26		0	TRIAC/ELV	NO					



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

