

JPCW-LED

Construction:

- Steel top, bottom and rings
- Diffuser is 0.80" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic
- Optional glass lenses are .125" thick


Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Integral mounting plate for standard "J-Box"
- Mounting orientation is downward
- Optional photocell attaches to wall mounting bracket, specify 120v or 277v
- Optional battery backup increase depth 1 1/2"
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



JPCW

Height - 12 1/2"

Width - 6 1/2"

Depth - 8 1/2"



ORDERING INFORMATION

Example: JPCW-LED-12-F2B-4-Z3-AHG

JPCW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
12-LED	F2B	12	1180	0-10v	NO	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster AHG Amber Honey Glass CSG Clear Seedy Glass	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v Consult Factory 90CRI Consult Factory ES Energy Star listed components 21 Photocell - See Notes -01 120 volt -02 277 volt Optional Voltage -347V Input voltage to 347v Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes
12-LED	F10	10	863	TRIAC/ELV	YES	Optional 3 3500K		Optional (See Price List) M17 Brass Powder		



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

