

# LSBW-LED

## Construction:

- Steel housing and chassis
- Diffuser white textured polycarbonate

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Center lockup for standard J-box
- Open top
- ADA compliant
- UL and CUL listed **DAMP** location
- Optional LED light sources

### Dedicated LED Replaceable Module

- Universal 120/277 volt standard
- Dimming 0-10v or Line Dim
- CRI > 80 or CRI > 90
- 5-Year Warranty on LED Components

### Socket based LED

- GU24 or medium base E26
- 120v
- CRI > 80 or CRI > 90
- Available as No lamp include **-NL**

### LSBW-9-LED

Height - 9"  
Width - 5"  
Depth - 4"

Type:	
Job Name:	



## ORDERING INFORMATION

Example: LSBW-9-LED-F1H-4-B1-WSP

### LSBW

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star					
9-LED	F1H	9	1400	0-10v	YES	2 3000K 4 4000K NL	B1 Satin Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W2 Gloss White W1 Yolk White Z1 Satin Bronze Z3 Text Bronze  Optional Finishes (see Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass	WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page  ES Energy Star listed components 90CRI Consult Factory  Optional Voltage -347V Input voltage to 347v  Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
	F1O	10	1065	TRIAC/ELV	YES					
	F1P	15	1724	TRIAC/ELV	YES					
	1E26		0	TRIAC/ELV	NO					
						Optional 3 3500K				



28435 Industry Drive., Valencia, California 91355  
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201  
East Coast Sales: 866-350-0991 • fax 866-490-5754  
www.lightwayind.com • sales@lightwayind.com

