

CAMC-LED

Construction:

- Steel housing and steel chassis
- Diffuser is .080" thick white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Optional battery backup - increases depth by 1 1/2"
- Optional Dimming driver
- UL and CUL listed **DAMP** location
- LED Array
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



CAMC-12

Height - 5"

Width - 11 1/2"

CAMC-16

Height - 7"

Width - 15 1/2"



ORDERING INFORMATION

Example: CAMC-LED-16-F1Q-4-B1-WTP

CAMC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K				
12-LED	F1L	9	1400	0-10v	YES	Optional 3 3500K	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WTP White Textured Polycarbonate WSP White Smooth Polycarbonate	DIM LED dimming driver (0 - 10v) DIMLD Line Voltage /TRIAC/ELV/120v See Resource Page	
	F1O	10	863	TRIAC/ELV	YES					
	F1P	15	1361	TRIAC/ELV	YES					
	F1K	13	2115	0-10v	YES					
16-LED	F1K	13	2115	0-10v	YES					90CRI Consult factory ES Energy Star listed components
	F1P	15	1361	TRIAC/ELV	YES				Optional Lens Material (see Price List)	OCCHFA Concealed Occupancy Sensor See Sensor Resource Sheet (Only available in 20 watt)
	F1Q	23	2057	TRIAC/ELV	YES				AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Optional Voltage -347V Input voltage to 347v
	L1A	36	4000	0-10v	NO					Battery Backup Options (Available with 0-10v only)
	O2C	18	2420	0-10v	NO				BB10 10 Watts (1170lm) for 90-Minutes	



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

