

MEDW-600-LED

Construction:

- Steel housing and chassis
- 3/8" Sq Accent bars and rings are extruded aluminum

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots top and bottom
- **Solid front shield allowing no forward light**
- **Down light only complies with Dark Sky requirements**
- Optional photocell (21) increases fixture depth 1 1/2"
- BUG Rating: B10U0G0
- Build America, Buy America Act Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components


Type:	
Job Name:	




DESIGN OPTIONS (Choose your cage design)



MERW-A



MERW-B



MERW-C^{D1}



MERW-D



MERW-E




MERW-F^{D1}




MERW-G^{D1}



MERW-H^{D1}



MERW-I



MERW-J



MERW-K^{D1}



MERW-X

Fixture Overall Dimensions

"H" - 12" - 16" - 18" - 26" - 38" - 50"



"W" - 6 1/2"

"D" - 4" 

"D1" - 4 3/8"

"MC" - 6" - 8" - 9" - 13" - 19" - 25"

- See 900 or 1100 Series for other width options



⁽¹⁾ Contact factory for assistance



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 www.lightwayind.com • sales@lightwayind.com



Revision: 08/12/2025

ORDERING INFORMATION

Example: MEDW-626-LED-G-F2B-4-B1

MEDW


Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 3 3500K 4 4000K 5 5000K	A B D E F G H I J K X	B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White W3 Text White T4 Shimmer Gray M13 Anod Silver T6 Pewter	Optional Cage Accents (See below)	DIM LED dimming driver (0 - 10v) 21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
612-LED	F2B	12	1180	0-10v	NO					
616-LED	F2B	12	1180	0-10v	NO				Material F Filigree P Perforated Screen M Wire Mesh W Waffle Pattern Style SC Screen Complete CC Center Complete EC Ends Complete CH Center Half OX Custom	OCCHFB Concealed Occupancy Sensor See Sensor Resource Sheet (0-10v Driver Engine only)
618-LED	F2B	12	1180	0-10v	NO					
626-LED	F2B	12	1180	0-10v	NO					
638-LED	F2B	12	1180	0-10v	NO					
650-LED	F2B	12	1180	0-10v	NO					
								Optional (See Price List) M17 Brass Powder P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass		Optional Voltage -347V Input voltage to 347v Battery Backup Options (0-10v Driver Engine only) BB10 10 Watts (1170lm) for 90-Minutes

OPTIONAL CAGE ACCENTS


(Not required, leave blank if undesired)

1) Optional Accent Location


(Shown as "A" cage. Others are Similar)




(SC)
Screen
Complete



(CC)
Center
Complete



(CH)
Center
Half




(EC)
End
Complete

2) Accent Material


(Required if Accent is chosen)




(S) Solid



(P) Perforated



(M) Mesh



(W) Waffle



(X) Custom⁽¹⁾

⁽¹⁾ Contact factory for assistance

ACCENT AVAILABILITY CHART BY CAGE STYLE

	A	B	C	D	E	F-H	I	J	K
SC	S,P,M,W	S,P,M,W	S,P,W	S,P,M,W		S,P,M,W	S,P,W	S,P,M,W	S,P,W
CC	S,P	S,P,M,W	S,P,W	S,P,M,W		S,P,M,W	---	---	S,P,W
CH	S,P,M,W	---	---	---		---	S,P,M,W	---	---

