# CJRC-LED

| | |
|---|---|
| **Type:** | |
| **Job Name:** | |

## Construction:

- Vandal resistant injection molded polycarbonate housing and lens

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Knockouts for standard "J-Box" mounting or conduit drill points for surface mounted conduit
- Vandal resistant polycarbonate
- UL and CUL listed **WET** location
- Driver operating temperature: -40C
- LED Components
  - Replaceable Module
  - CRI > 90
  - 5-Year Warranty on LED Components



**CJRC-11-LED**
Height - 3.94"
Diameter - 11.87"

DIMMABLE

c UL us LISTED

MADE IN AMERICA

## ORDERING INFORMATION

**Example: CJRC-11-LED-O2A-4-B99-WSP**

### CJRC

| Size | LED | Watts | Source Lumens | Dimming | Energy Star |
|---|---|---|---|---|---|
| | | | | | |
| **11-LED** | **O2A** | 12 | 1600 | 0-10v | NO |
| | **O3A** | 14 | 2240 | 0-10v | NO |
| | **O4A** | 18 | 2880 | 0-10v | NO |

**Kelvin**

**2** 3000K
**3** 3500K
**4** 4000K

**Cage**

**Finish**

**B99** Black

**Optional Finishes**
(see Price List)

**W99** White

**Diffuser**

**WSP** White Smooth Polycarbonate

**Options**

**DIM** LED dimming driver (0 - 10v)

**21** Photocell - *See Notes*
-**01** 120 volt
-**02** 277 volt

28435 Industry Drive., Valencia, California 91355
800-325-4448 /661-257-0286• fax 800-323-2346 /661-257-0201
www.lightwayind.com • sales@lightwayind.com

Lightway

Revision: 11/18/2026