

# WPHW-LED

## Construction:

- Cast aluminum housing
- Aluminum reflector
- Clear tempered glass lens

## Light Source:

- LED
- Dimming to 10% **Included**

## Notes:

- Wall mounting bracket attaches to 4" recessed outlet box
- Up/down light standard; aluminum cover to convert to down light only (UPD – option); **NOT TO BE USED WITH UP LIGHT ONLY**
- Dark Sky compliant - downlight only
- Optional battery backup
- Optional photocell
- CSA listed **WET** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

### WPHW-7

Height - 7"

Width - 14 1/2"

Depth - 7"

Type:	
Job Name:	



## ORDERING INFORMATION

Example: WPHW-7-LED-O1B40-3-Z99-CEG

### WPHW

Size	LED					Kelvin	Cage	Finish	Diffusers	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		Z99 Bronze	CEG Clear Tempered Glass	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% ( <b>Included</b> )
7-LED	O1B40	29	5025	0-10v	NO	Optional 3 3500K				21 Photocell - <i>See Notes</i> -01 120 volt -02 277 volt
	O1B20	15	2563	0-10v	NO					UPD - down light only
<ul style="list-style-type: none"> <li>• O1B40 - Up &amp; Down configuration only</li> </ul>										<b>Battery Backup Options</b> <i>(Available with 0-10v only)</i> <b>BB10</b> 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

